

W48M

Key Specs

Engine Manufacturer/Model - FS481V
Engine Power - At 3600 rpm 14.5 hp* / 10.8 kW
Fuel Tank Capacity - 5.4 U.S. gal.
Transmission - Two Hydro-Gear ZT-2800 unitized pump and wheel motor transmissions and ergonomic handles with spring-loaded neutral lock
Drive Wheels - 18x8.5-8
Caster Wheels - 9x3.5-4 semi-pneumatic
Speed Range - Forward - 6.5 mph
Speed Range - Reverse - 3.0 mph
Mower Deck Size - 48.0 in.
Blade Tip Speed - 18000.0 fpm
Warranty - 24 month

Engine

Engine Manufacturer/Model - FS481V
Engine Power - At 3600 rpm 14.5 hp* / 10.8 kW
Displacement - 36.8 cu in.
Cylinders - V-twin
Operating Speed - 3600.0 rpm
Ignition/Starter - Electronic/recoil start
Valving - Overhead valves
Oil Filter - Standard
Lubrication - Full pressure

Engine

Governor - Flyweight all speed governor

Hour Meter - Standard, digital

Cooling System - Air cooled

Air Cleaner - Paper element with foam precleaner

Muffler - Low tone

Fuel System

Fuel Type - Gasoline

Fuel Tank Capacity - 5.4 U.S. gal.

Fuel Pump - Vacuum-operated diaphragm

Fuel Delivery System - Carburetor

Fuel Tank Switch/Shut Off Valve - No

Fuel Pickup - Top draw

Electrical System

Ignition - Electronic spark

Hourmeter - Standard, digital

Operator Presence Starting System - PTO off, park brake engaged, speed lever in neutral

Drivetrain

Transmission - Two Hydro-Gear ZT-2800 unitized pump and wheel motor transmissions and ergonomic handles with spring-loaded neutral lock

Shift Mechanism - Ergonomic handles with spring-loaded neutral lock

Tires

Drive Wheels - 18x8.5-8

Caster Wheels - 9x3.5-4 semi-pneumatic

Travel Speed

Forward Speeds - Infinite

Reverse Speeds - Infinite

Speed Range - Forward - 6.5 mph

Speed Range - Reverse - 3.0 mph

Brakes

Type - Dynamic braking with hand controls, hand lever to set parking brake

Dimensions

Height - 44.8 in.

Length With Deck - 74.0 in.

Width - Deflector Down - 62.0 in.

Width - Deflector Up For Storage - 50.0 in.

Weight - 645.0 lb.

Mower Decks

Mower Deck Size - 48.0 in.

Material - 10-gauge, 0.14-in. (3.42-mm) fabricated steel deck top with added 10-gauge, 0.14-in. (3.42-mm) spindle mounting plate, 7-gauge, 0.19-in. (4.8-mm) side skirts with reinforcement bar

Blades - Three high-lift

Blades - Length - 16.5 in.

Blades - Thickness - 0.25 in.

Blade Drive - V-Belt

Blade Tip Speed - 18000.0 fpm

Cutting Height - 1.5-4.5 in.

Buyer's note

Warranty - 24 month

Additional Information

Date Collected - 2022-07-11T00:00:00