



Z760R

Key Specs

Engine Power - 27.0 hp

Engine Model Number - FX850V

Forward Speed - 10.0 mph

Front Caster Tires - 13x6.5-6

Drive Tires - 24X12-12 (54- and 60-in. decks) / Optional - 24X12N12 Michelin® Tweel® X Turf Airless Radial

Seat Back Height - 24.0 in.

Cutting Width - 54/60 in.

Warranty - 4 year/1000 hour bumper-to-bumper* (*Term limited to years or hours used, whichever comes first, and varies by model. See the LIMITED WARRANTY FOR NEW JOHN DEERE TURF AND UTILITY EQUIPMENT at JohnDeere.com or JohnDeere.ca/TUWarranty for details.)

Mulching System - Optional MulchControl™ attachment

Engine

Engine Power - 27.0 hp

Engine Model Number - FX850V

Displacement - 52.0 cu in.

Cylinders - V-twin

Lubrication - Full pressure with replaceable filter

Lubrication - 2.4 U.S. qt

Type - Overhead valve

Battery Cold Crank Amps - 340.0 CCA

Choke/Speed Control - Separate control levers

Cooling Method - Air

Engine

Fuel Tank Capacity - 8.0 U.S. gal.

Fuel Gauge - Fuel level sight line

Drivetrain

Dual Hydros - Hydro-gear ZT3400 with 1-in. (2.54-cm) axles

Travel Speed

Forward Speed - 10.0 mph

Reverse Speed - 4.5 mph

Speed And Direction Control - Twin premium levers

Control Adjustment - 2-height/18 positions

Chassis

Frame - Heavy-duty frame tubing

Primer/Paint - E-coat/powder

Front Caster Tires - 13x6.5-6

Front Caster Bearings - Sealed ball bearings

Drive Tires - 24X12-12 (54- and 60-in. decks) / Optional - 24X12N12 Michelin® Tweel® X Turf Airless Radial

Hour Meter - Yes with low oil pressure and low battery voltage indicators

Service Interval Decal - Yes

Storage Compartment - Yes

Cup Holder - Yes

Seat

Seat Back Height - 24.0 in.

Fore-Aft Adjustment - 4.0 in.

Seat Suspension - Mechanical; adjustable for weight with ComfortGlide™

Lift System

Type - Spring assisted foot lift

Mower Cut Height - Minimum - 1.5 in.

Mower Cut Height - Maximum - 5.0 in.

Cut Height Increments - 0.25 in.

Preset Cut Height - Yes

Mower Deck

Cutting Width - 54/60 in.

Type - High-capacity (HC) PRO side discharge

Mower Deck Material - 9.0 gauge

Mower Deck Material - 0.15 in.

Mower Drive System - V-belt

Power Take-Off (PTO)

Type - Electric

Type - 125.0 lb-ft

Drive - V-belt

Dimensions

Wheelbase - 49.9 in.

Overall Length - 82.0 in.

Operation

Rollover Protective Structure (ROPS) - Yes

Slope Operating Limit - Standard: 15 degrees; With Material Collection System: 10 degree (angle)

Operator Presence System - Yes

Park Brake Interlock - Yes

Operator Video - Yes

Buyer's Notes

Note 1 - Flip-up and adjustable foot platform for easy service access

Warranty - 4 year/1000 hour bumper-to-bumper* (*Term limited to years or hours used, whichever comes first, and varies by model. See the LIMITED WARRANTY FOR NEW JOHN DEERE TURF AND UTILITY EQUIPMENT at JohnDeere.com or JohnDeere.ca/TUWarranty for details.)

Optional Attachments

Mulching System - Optional MulchControl™ attachment

Rubber Floor Mat - Standard

Light Kit - Standard LED work and optional beacon lights

Material Collection System - 54 HC PRO, and 60 HC PRO Power Flow™ rear bagger / Not compatible with Tweel option

Material Collection System - 6.5 bu

Additional Information

Date Collected - 2022-12-01T00:00:00