



X390 (48-in. Deck)

Key Specs

Engine Power - 23.0 hp

Engine Manufacturer/Model - FR691V

Transaxle Type - K58 hydrostatic integrated with transaxle

Transaxle Control - Twin Touch™ pedals

Rear Tires - 22x11-10

Lift System Type - Hydraulic

Cutting Width - 48 in.

Warranty - 4 year/300 hour bumper-to-bumper* (*Term limited to years or hours used, whichever comes first, and varies by model. See the LIMITED WARRANTY FOR NEW JOHN DEERE TURF AND UTILITY EQUIPMENT at JohnDeere.com or JohnDeere.ca/TUWarranty for details.)

Engine

Engine Power - 23.0 hp

Displacement - 44.3 cu in.

Engine Manufacturer/Model - FR691V

Engine Type - Overhead valve, full-pressure lube, oil filter

Cylinders - V-twin, cast-iron liners

Governor - Mechanical

Choke/Speed Control - Separate levers, automatic choke return

Cooling Method - Air

Air Cleaner - Dry, replaceable

Oil Change - No-tools oil drain with replaceable filter

Fuel System

Type - Gasoline

Fuel Delivery - Pulse pump, carburetor

Fuel Gauge - Gauge on dash

Fuel Tank Location - Rear

Fuel Fill Opening - On left fender

Fuel Fill Opening - 3.0 in.

Fuel Tank Capacity - 3.3 U.S. gal.

Electrical System

Battery Cold Crank Amps - 340.0 CCA

Charging System - Flywheel alternator, regulated

Charging System - 12.0 amp

Engine Starter - Bendix

Hour Meter - Yes

Headlights - Two standard, incandescent, 27 W

Taillights Or Reflector - No

Backup Lights - No

Rear Work Lights - No

12-V Outlet - Optional

Transaxle

Transaxle Type - K58 hydrostatic integrated with transaxle

Transaxle Control - Twin Touch™ pedals

Cruise Control - Yes, button on dash

Oil Cooler - Fins and fan on transaxle

Oil Filter - Internal, not replaceable

Differential Lock - No

Forward Speed - 6.2 mph

Reverse Speed - 3.5 mph

Brakes - Internal wet disc

Chassis

Frame - Welded heavy-duty

Primer/Paint - E-coat/powder

Chassis

Weight Bracket - Standard rear, optional front

Receiver Hitch - No

Front Axle - Cast iron front axle, front wheel ball bearings

Spindle Bushings - Metal, replaceable

Front Tires - 15x6.5-8

Rear Tires - 22x11-10

Hood Material - Fully enclosed, molded-in color material reduces sound, will not rust or dent

Fender Deck Material - Stamped steel

Floor Mats - Sure-grip rubber

Storage - Yes, under seat and covered toolbox

Service Interval Decal - Yes

Fender Handles/Grips - No

Cup Holder - Yes

Equipment Mounting - Yes, heavy duty

Maximum Towing Capacity - 600.0 lb.

Steering

Type - Power, hydraulic

Four-Wheel Steer - Not available on this model

Steering Wheel - 14.0 in.

Tilt Steering Wheel - Standard, five position

Turning Radius - 22.0 in.

Uncut Circle Radius - 24.0 in.

Seat

Type - Cut-and-sewn high-back

Seat Back Height - 18.0 in.

Armrests - Optional

Fore-Aft Adjustment - 6.6 in.

Seat Suspension - Tilt, two coil springs, three-position no-tools adjustment for operator weight

Lift System

Lift System Type - Hydraulic

Hydraulic Outlets - No

Lift System

Mower Cut Height - Minimum - 1.0 in.

Mower Cut Height - Maximum - 4.0 in.

Cut Height Increments - 0.25 in.

Preset Cut Height - Yes

Mower Deck

Type - Side discharge

Cutting Width - 48 in.

Construction - Forged steel deck shell

Mower Deck Material - 10.0 gauge

Mower Deck Material - 0.135 in.

Mower Wash Port - Yes

Mower Drive System - Electric power take-off (PTO) clutch, in-line belt

Mower Wheels - Four

Mower Wheel Adjustment - Seven-position, spring-loaded pin

Mower Level Adjustment - Exact Adjust ports and onboard deck-leveling gauge

Mower Attachability

Type - Roll under tractor

Front Draft Arms - Attached with spring pins at two points

Rear Draft Arms - Quick-pull pins

Mower Wheels Rotate - Yes, 90 degrees for easy mower removal

Drive System - Dual belt

Safety

Meets ANSI Standard - Yes

Meets OPEI Standard - Yes

Backup Protection - Reverse Implement Option (RIO)

Safety Video - Yes

Buyer's Notes

Notes - Hydraulic power lift for superior convenience and ease of use
Power steering with tilt steering wheel for exceptional maneuverability and comfort
Fully enclosed, molded-in color material reduces sound, will not rust or dent

Warranty - 4 year/300 hour bumper-to-bumper* (*Term limited to years or hours used, whichever comes

Buyer's Notes

first, and varies by model. See the LIMITED WARRANTY FOR NEW JOHN DEERE TURF AND UTILITY EQUIPMENT at JohnDeere.com or JohnDeere.ca/TUWarranty for details.)

Optional Equipment

Mowers - 48A (standard)

Rear Bagger - 19.0 bu

Powered Material Collection - Power Flow™ blower

Mulching System - Yes, MulchControl™

Front Thatcher - 54.0 in.

Front Blade - 44.0 in.

Snow Blower - 44.0 in.

Sprayer - Tow-Behind - 25.0 U.S. gal.

Sprayer - Mounted - 25.0 U.S. gal.

Spreader - Tow-Behind - 175.0 lb.

Spreader - Mounted - 125.0 lb.

Front Bumper - Styled bumper option

Brush Guard - Yes

Weather Protection - Weather enclosure

Sun Canopy - Yes

Bucket Holder - Yes, double bucket

Grass Striping - Lawn striping kit

Tractor Shovel - 40.0 in.

Tow-Behind Tools - 16

Dimensions

Height - 49.0 in.

Overall Length - 72.3 in.

Wheelbase - 49.4 in.

Width With Mower - 62.6 in.

Width With Mower (Deflector Raised For Storage) - 52.6 in.

Width Without Mower - 39.4 in.

Weight - 678.0 lb.

Additional Information

Additional Information

Manufacturing Location - Horicon, Wisconsin, USA

Date Collected - 2022-10-03T00:00:00