



Z315E

Key Specs

Engine Power - 20.0 hp

Engine Model Number - 40 EXi

Forward Speed - 7.0 mph

Front Caster Tires - 11x6-5

Drive Tires - 18x8.5-8

Seat Back Height - 18.0 in.

Cutting Width - 42 in.

Warranty - 3 year or 200 hour bumper-to bumper* (*Term limited to years or hours used, whichever comes first, and varies by model. See the LIMITED WARRANTY FOR NEW JOHN DEERE TURF AND UTILITY EQUIPMENT at JohnDeere.com or JohnDeere.ca/TUWarranty for details.)

Mulching System - Optional MulchControl™ attachment

Engine

Engine Power - 20.0 hp

Engine Model Number - 40 EXi

Displacement - 40.0 cu in.

Cylinders - V-twin

Lubrication - Full pressure with replaceable filter

Lubrication - 2.0 U.S. qt

Type - Overhead valve

Battery Cold Crank Amps - 300.0 CCA

Choke/Speed Control - Single lever

Cooling Method - Air

Engine

Fuel Tank Capacity - 3.0 U.S. gal.

Fuel Gauge - Translucent tank

Drivetrain

Dual Hydros - Hydro-Gear EZT-C with 1-in. (2.5-cm) axles

Travel Speed

Forward Speed - 7.0 mph

Reverse Speed - 3.5 mph

Speed And Direction Control - Twin levers

Control Adjustment - 3 height, 11 positions

Chassis

Frame - Heavy-duty 2.5-in. x 2-in. (6-cm x 5-cm) front, and 1.5-in. x 2-in. (4-cm x 5-cm) side tubing

Primer/Paint - E-coat/powder

Front Caster Tires - 11x6-5

Front Caster Bearings - Sealed ball bearings

Drive Tires - 18x8.5-8

Hour Meter - Yes

Service Interval Decal - Yes

Storage Compartment - Optional covered

Cup Holder - Yes

Maximum Towing Capacity - 250.0 lb.

Seat

Seat Back Height - 18.0 in.

Fore-Aft Adjustment - 2.9 in.

Seat Suspension - Two springs

Lift System

Type - Foot lift

Mower Cut Height - Minimum - 1.25 in.

Mower Cut Height - Maximum - 4.5 in.

Cut Height Increments - 0.25 in.

Lift System

Preset Cut Height - Yes

Mower Deck

Cutting Width - 42 in.

Type - Side discharge

Mower Deck Material - 12.0 gauge

Mower Deck Material - 0.105 in.

Mower Drive System - V-belt

Power Take-Off (PTO)

Type - Electric

Type - 105.0 lb-ft

Drive - V-belt

Dimensions

Wheelbase - 49.4 in.

Overall Length - 75.4 in.

Width Without Mower - 43.3 in.

Width With Mower - 50.4 in.

Width With Mower (Deflector Raised For Storage) - 46.5 in.

Height - 41.6 in.

Weight - 554.0 lb.

Operation

Rollover Protective Structure (ROPS) - No

Slope Operating Limit - Standard: 13 degrees; With Material Collection System: 10 degree (angle)

Operator Presence System - Yes

Park Brake Interlock - Yes

Operator Video - Yes, online

Buyer's Notes

Note 1 - Durable Accel Deep Mower Decks are made from 12-gauge steel with double captured mower wheels

Note 2 - Easily change cut height from 1.25 to 4.5 in. (3 to 11 cm) using the foot lift and cutting height dial

Buyer's Notes

Note 3 - Integrated park brake is automatically applied when steering levers are stowed outward

Warranty - 3 year or 200 hour bumper-to bumper* (*Term limited to years or hours used, whichever comes first, and varies by model. See the LIMITED WARRANTY FOR NEW JOHN DEERE TURF AND UTILITY EQUIPMENT at JohnDeere.com or JohnDeere.ca/TUWarranty for details.)

Optional Attachments

Mulching System - Optional MulchControl™ attachment

Rubber Floor Mat - Optional

Sun Shade - Optional

Mounted Sprayer - Not available U.S. gal.

Protective Cover - Optional

Light Kit - Optional

Material Collection System - Two-bag cut-and-throw MCS

Material Collection System - 6.5 bu

Additional Information

Manufacturing Location - Greeneville, Tennessee, USA

Date Collected - 2022-10-03T00:00:00