



Z530R

Key Specs

Engine Power - 24.0 hp

Engine Model Number - FR730V

Forward Speed - 9.0 mph

Front Caster Tires - 13x6.5-6

Drive Tires - 23x10.5-12

Seat Back Height - 22.5 in.

Cutting Width - 48/54/60 in.

Warranty - 4 year/500 hour bumper-to-bumper* (*Term limited to years or hours used, whichever comes first, and varies by model. See the LIMITED WARRANTY FOR NEW JOHN DEERE TURF AND UTILITY EQUIPMENT at JohnDeere.com or JohnDeere.ca/TUWarranty for details.)

Mulching System - Optional MulchControl attachment, 54 in. / 137 cm / Optional MulchControl kit, 60 in. / 152 cm

Engine

Engine Power - 24.0 hp

Engine Model Number - FR730V

Displacement - 44.3 cu in.

Cylinders - V-twin

Lubrication - Full pressure with replaceable filter

Lubrication - 2.0 U.S. qt

Type - Overhead valve

Battery Cold Crank Amps - 300.0 CCA

Choke/Speed Control - Separate control levers

Cooling Method - Air

Engine

Fuel Tank Capacity - 4.5 U.S. gal.

Fuel Gauge - Electric gauge and fuel level sight line

Drivetrain

Dual Hydros - Tuff Torq TZT7-M with 1-in. (2.5-cm) axles

Travel Speed

Forward Speed - 9.0 mph

Reverse Speed - 4.5 mph

Speed And Direction Control - Twin levers

Control Adjustment - 2-height/9-fore-aft, 18 positions

Chassis

Frame - Heavy-duty frame tubing

Primer/Paint - E-coat/powder

Front Caster Tires - 13x6.5-6

Front Caster Bearings - Sealed ball bearings

Drive Tires - 23x10.5-12

Hour Meter - Yes

Service Interval Decal - Yes

Storage Compartment - Yes and covered

Cup Holder - Yes

Maximum Towing Capacity - 250.0 lb.

Seat

Seat Back Height - 22.5 in.

Fore-Aft Adjustment - 3.0 in.

Seat Suspension - Two springs and ComfortGlide

Lift System

Type - Foot lift

Mower Cut Height - Minimum - 1.0 in.

Mower Cut Height - Maximum - 4.0 in.

Cut Height Increments - 0.25 in.

Lift System

Preset Cut Height - Yes

Mower Deck

Cutting Width - 48/54/60 in.

Type - High-capacity side discharge

Mower Deck Material - 9.0 gauge

Mower Deck Material - 0.15 in.

Mower Drive System - V-belt

Power Take-Off (PTO)

Type - Electric

Type - 125.0 lb-ft

Drive - V-belt

Dimensions

Wheelbase - 49.2 in.

Overall Length - 81.9 in.

Width Without Mower - 48.7 in.

Operation

Rollover Protective Structure (ROPS) - Yes

Slope Operating Limit - Standard: 15 degrees; With Material Collection System: 10 degree (angle)

Operator Presence System - Yes

Park Brake Interlock - Yes

Operator Video - Yes

Buyer's Notes

Note 1 - Mower wash port makes cleaning the deck easier

Note 2 - Flip-up foot platform for easy service access

Note 3 - 18-position adjustable motion-control levers

Warranty - 4 year/500 hour bumper-to-bumper* (*Term limited to years or hours used, whichever comes first, and varies by model. See the LIMITED WARRANTY FOR NEW JOHN DEERE TURF AND UTILITY EQUIPMENT at JohnDeere.com or JohnDeere.ca/TUWarranty for details.)

Optional Attachments

Optional Attachments

Mulching System - Optional MulchControl attachment, 54 in. / 137 cm / Optional MulchControl kit, 60 in. / 152 cm

Rubber Floor Mat - Foot platform and toe board

Sun Shade - Optional

Mounted Sprayer - No U.S. gal.

Protective Cover - Yes

Light Kit - 4-point LED Light kit

Material Collection System - Power Flow rear bagger / Not available on 60HC

Material Collection System - 6.5 bu

Additional Information

Manufacturing Location - Greeneville, Tennessee, USA

Date Collected - 2021-12-01T00:00:00