



4066M

Key Specs

Displacement - 127 cu in.

Rated Engine Power - 65 hp: (SAE J1995)

Rated Engine Power - 66 PS

Machine Configuration

Wheel or Track Configuration - Wheel

Engine

Emissions Certifications - Final Tier 4

Displacement - 127 cu in.

Aspiration - Turbocharged and charge air cooled

Number of Cylinders - 4

Cylinder Liners - Cast-in-block

Rated Engine Speed - 2600 rpm

Rated Engine Power - 65 hp: (SAE J1995)

Rated Engine Power - 66 PS

Compression Ratio - 19.1:1

Lubrication - Pressurized

Cooling System Type - Liquid

Fuel Type - Diesel; High-pressure common rail direct injection

Air Cleaner Type - Dual element

Transmission

Clutch - Wet

Cruise Control - Optional

Rear Power Take-Off (PTO)

Economy PTO Speeds - 540 rpm

Engagement Method - Independent

PTO Clutch - Wet disc

Rear Hitch

Draft Control Sensing - Position control

Hydraulics

Hydraulic System Type - Open center

Auxiliary Hydraulic Features - Up to six rear remote control valves available

Front Axle

Front Axle Differential Lock - Yes

Rear Axle

Final Drive - Planetary

Steering & Brakes

Primary Brakes - Multi-plate wet disc

Tires

Front Tires Size - 8-16 (Farm), 27x10.5-15 (Turf), 10-16.5 (Industrial)

Electrical System

Alternator Capacity - 75 amp

Operator Station

Gearshift Location - PowrReverser - Left-hand side