

REPLACEMENT PARTS GUIDE

3038E Tractor (PIN: 1LV3038E*LL300001-) (Worldwide Edition)

ENGINE



ENGINE OIL

[TY26668](#) (John Deere Plus-50™ II Premium)
(10W-30) 4.5 L (4.7 qt)) (WITH FILTER)
Change every 400 hrs/ Annually



SPIN-ON FUEL FILTER

[MIU800645](#) (PRIMARY)
[MIU803127](#) (SECONDARY)

Change after every 400 Hrs/Annually.



AIR FILTER

[M131802](#) (PRIMARY AIR CLEANER
ELEMENT)
[M131803](#) (SECONDARY AIR CLEANER
ELEMENT)

Service every 600 hrs. Change as required.



JD MULTI PURPOSE HD LITHIUM COMPLEX GREASE

[TY24416](#)
[TY26183](#)

Change As Required.



OIL FILTER

[M806419](#)
Change every 400 hrs/ Annually.



FUEL-WATER SEPARATOR

[MIU802421](#) (FILTER ELEMENT)
Change after every 400 Hrs.



FILTER PAK

[LVA21037](#)

AXLE



TIE ROD

[LVA15994](#) (ASSEMBLY)
[LVA15995](#) (LH)
[LVA15996](#) (RH)



FRONT AXLE OIL

[TY22035](#) (John Deere Low Viscosity
Hy-Gard™) (3.8 L (4 qt))
Change every 600 Hrs.



ELECTRICAL



KEY

[LVU33004](#)



ROTARY SWITCH

[LVA21501](#) (14 V)



WET DISCHARGE BATTERY

[TY27831B](#) (12 V, 45 AH)



LED WORK LIGHT

[AM143579](#) (OOS) (12 V)



HEADLIGHT

[LVA23717](#) (LH) (TRAFFIC, DRIVING LIGHT)
[LVA23716](#) (DRIVING LIGHT)



V - BELT

[LVU30203](#) (LGTH = 995 mm,
WIDTH = 13.7 mm, TK = 9.5 mm)
[LVU33849](#) (LGTH = 975 mm,
WIDTH = 13.7 mm, TK = 9.5 mm)

FUEL TANK FILLER CAP



FILLER CAP
[AL213202](#)

TRANSMISSION/ HYDRAULIC



TRANSMISSION/HYDRAULIC OIL

[TY22000](#) (John Deere Low Viscosity
Hy-Gard™) (20.8 L (5.5 gal))
Change every 400 hrs.



OIL FILTER

[LVA16054](#) (CHARGE HYDRAULIC FILTER)
[LVA14703](#) (SUCTION HYDRAULIC FILTER)
Change every 400 hrs.